


DATA SHEET POLYMAX 1M12B

UPDATED: MAY 2012

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	80 SHORE A
	Cover structure	SMOOTH		Bottom cover	80 SHORE A
	Colour	BLACK	ANTISTATIC PROPERTIES YES		
INTERMED. LAYER	Material	-	TEMPERATURE RANGE		
	Colour	-			
BOTTOM COVER	Material	PVC	PULLEY-DIAMETER		
	Cover	NEGATIV PYRAMIDE			
	Colour	BLACK			
UPPER FABRIC	Warp	-			
	Weft	-			
INTERMED.FABRIC	Warp	-	<u>1: Normal flex</u> min Ø = 35 [mm]		
	Weft	-	<u>2: Back flex</u> min Ø = 50 [mm]		
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.) 12 [N/mm]		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% 8 +/-0.5 [N/mm]		
TOP COVER THICKNESS		0.60 [mm]	WEIGHT 1.80 [Kg/m2]		
BOTTOM COVER THICKNESS		0.50 [mm]	COEF.FRICTION (STEEL) 0.5 +/-0.1		
TOTAL THICKNESS		1.70 [mm]	APPROVAL		

ADDITIONAL INFORMATION	
SPECIAL FEATURES	RIGID
APPLICATIONS	AGRICULTURAL INDUSTRY DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ELETRONICS INDUSTRY TEXTILE INDUSTRY
JOINING METHODS	SINGLE FINGER SPLICING MECHANICAL SPLICING

