


DATA SHEET

POLYMAX 2M020G-SG-P8

UPDATED: DEC 2020

CONSTRUCTION		DATA		
TOP COVER	Material	PVC	HARDNESS	
	Cover structure	SUPER GRIB		Top cover 40 SHORE A
	Colour	PETROL GREEN	Bottom cover - SHORE A	
INTERMED. LAYER	Material	PVC	ANTISTATIC PROPERTIES YES	
	Colour	PETROL GREEN	TEMPERATURE RANGE	
BOTTOM COVER	Material	-		
	Cover	FABRIC	Max. 70 ° C	
UPPER FABRIC	Warp	POLYESTER	PULLY-DIAMETER	
	Weft	POLYESTER/MONOFIL		
INTERMED.FABRIC	Warp	-		
	Weft	-		
BOTTOM FABRIC	Warp	POLYESTER	Min. Ø 50 [mm]	
	Weft	POLYESTER/MONOFIL	<u>2: Back flex</u>	
TOP COVER THICKNESS	3,50 [mm]		Min. Ø 100 [mm]	
BOTTOM COVER THICKNESS	- [mm]		WORKING TENSION (NOM.) 20 [N/mm]	
TOTAL THICKNESS	5,13 [mm]		PULL FOR ELONGATION 1% (MIN.) 8 +/- 1 [N/mm]	
			WEIGHT 4,44 [Kg/m2]	
			COEF.FRICTION (STEEL) 0,14 +/- 0,03 [mm]	
			APPROVAL	

ADDITIONAL INFORMATION	
APPLICATIONS	INCREASING TRANSPORT (LIGHT) PACKAGE LINES PACKAGED ITEMS (BAGS, BAGS AND BOXES) PAPER INDUSTRY (STABLING) DISTRIBUTION (POST, NEWSPAPERS, AIRPORTS, TERMINALS)
JOINING METHODS	DOUBLE FINGER JOINING OVERLAP JOINING MECHANICAL JOINING
	