


DATA SHEET

POLYMAX 2M24AG

UPDATED: MAY 2012

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	80 SHORE A
	Cover structure	SMOOTH		Bottom cover	80 SHORE A
	Colour	APPELGREEN	ANTISTATIC PROPERTIES YES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	APPELGREEN			
BOTTOM COVER	Material	PVC	Max.	70 ° C	
	Cover	NEGATIV PYRAMIDE	PULLEY-DIAMETER		
	Colour	APPELGREEN			
UPPER FABRIC	Warp	POLYESTER			
	Weft	POLYESTER/MONOFIL			
INTERMED.FABRIC	Warp	-	WORKING TENSION (NOM.) 24 [N/mm]		
	Weft	-	PULL FOR ELONGATION 1% 10.5 +/-0.5 [N/mm]		
BOTTOM FABRIC	Warp	POLYESTER	WEIGHT 3.45 [Kg/m2]		
	Weft	POLYESTER/MONOFIL	COEF.FRICTION (STEEL) 0.57 +/-0.1		
TOP COVER THICKNESS		0.70 [mm]	APPROVAL -		
BOTTOM COVER THICKNESS		0.70 [mm]			
TOTAL THICKNESS		3.10 [mm]			

ADDITIONAL INFORMATION	
SPECIAL FEATURES	BASE FOR POLYFLEX SIDEWALLS (ASCENDING TRANSPORT)
APPLICATIONS	FRUITS AND VEGETABLES DISTRIBUTION (POST, NEWSPAPERS, AIRPORTS, TERMINALS) PLUCKING AND SORTING TOBACCO INDUSTRY TEA INDUSTRI PAPER INDUSTRY ALL ROUND TRANSPORT (MEDIUM HEAVY) ELECTRONICS INDUSTRY
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

