


DATA SHEET POLYMAX 2M24B

UPDATED: MAY 2012

CONSTRUCTION			DATA			
TOP COVER	Material	PVC		HARDNESS	Top cover	80 SHORE A
	Cover structure	SMOOTH			Bottom cover	80 SHORE A
	Colour	BLACK		ANTISTATIC PROPERTIES YES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE	Min.	-10 ° C	
	Colour	BLACK		Max.	70 ° C	
BOTTOM COVER	Material	PVC	PULLEY-DIAMETER			
	Cover	NEGATIV PYRAMIDE		<u>1: Normal flex</u>		
Colour	BLACK	min Ø =		50 [mm]		
UPPER FABRIC	Warp	POLYESTER	<u>2: Back flex</u>			
	Weft	POLYESTER/MONOFIL	min Ø =	70 [mm]		
INTERMED.FABRIC	Warp	-	WORKING TENSION (NOM.) 24 [N/mm]			
	Weft	-	PULL FOR ELONGATION 1% 10.5 +/-0.5 [N/mm]			
BOTTOM FABRIC	Warp	POLYESTER	WEIGHT 3.45 [Kg/m2]			
	Weft	POLYESTER/MONOFIL	COEF.FRICTION (STEEL) 0.57 +/-0.1			
TOP COVER THICKNESS		0.70 [mm]	APPROVAL -			
BOTTOM COVER THICKNESS		0.60 [mm]				
TOTAL THICKNESS		3.10 [mm]				

ADDITIONAL INFORMATION	
SPECIAL FEATURES	BASE FOR POLYFLEX SIDEWALLS (ASCENDING TRANSPORT) RIGID
APPLICATIONS	AGRICULTURAL INDUSTRY WOOD INDUSTRY (CHIP BOARDS) PAPIER INDUSTRY DISTRIBUTION (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ALL ROUND TRANSPORT
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

