


DATA SHEET

POLYMAX 2M24BL FDA NP

UPDATED: MAY 2012

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	65 SHORE A
	Cover structure	SMOOTH		Bottom cover	65 SHORE A
	Colour	BLUE	ANTISTATIC PROPERTIES NO		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	BLUE			
BOTTOM COVER	Material	PVC	PULLEY-DIAMETER		
	Cover	NEG. PYRAMID			
	Colour	BLUE			
UPPER FABRIC	Warp	POLYESTER			
	Weft	POLYESTER/MONOFIL			
INTERMED.FABRIC	Warp	-	<u>1: Normal flex</u> min Ø = 60 [mm]		
	Weft	-	<u>2: Back flex</u> min Ø = 90 [mm]		
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.) 24 [N/mm]		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% 10.5 +/-0.5 [N/mm]		
TOP COVER THICKNESS		1.00 [mm]	WEIGHT 3.45 [Kg/m ²]		
BOTTOM COVER THICKNESS		0.70 [mm]	COEF.FRICTION (STEEL) 0.3 +/- 0.1		
TOTAL THICKNESS		3.60 [mm]	APPROVAL USDA and FDA according to EU's 90/128/EU & EC1935/2004 - all updated directives included.		

ADDITIONAL INFORMATION	
SPECIAL FEATURES	BASE FOR POLYFLEX SIDEWALLS (ASCENDING TRANSPORT) CONTRAST COLOUR FOR WHITE MEAT, FISH A.O.
APPLICATIONS	FOOD INDUSTRY IN GENERAL FISH PROCESSING INDUSTRY MEAT PROCESSING IN GENERAL POULTRY SLAUGHTERHOUSES BAKERIES FRUITS AND VEGETABLES SHELLFISH DAIRYWORKS AND CHEESE PRODUCTION
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

