


DATA SHEET

POLYMAX 2T024W FDA

UPDATED: MAY 2012

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	65 SHORE A
	Cover structure	SMOOTH		Bottom cover	- SHORE A
	Colour	WHITE	ANTISTATIC PROPERTIES NO		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	WHITE			
BOTTOM COVER	Material	-	Max.	90 ° C	
	Cover	FABRIC	PULLEY-DIAMETER		
	Colour	-			
Warp	POLYESTER	<u>1: Normal flex</u>			
UPPER FABRIC	Weft	POLYESTER	<u>2: Back flex</u>	min Ø = 80 [mm]	
	Warp	-	WORKING TENSION (NOM.) 24 [N/mm]		
INTERMED.FABRIC	Weft	-	PULL FOR ELONGATION 1% 15 +/-1 [N/mm]		
	Warp	POLYESTER	WEIGHT 2.90 [Kg/m ²]		
BOTTOM FABRIC	Weft	POLYESTER	COEF.FRICTION (STEEL) 0.15 +/-0.03		
	TOP COVER THICKNESS	0.70 [mm]	APPROVAL USDA and FDA according to EU's 90/128/EU & EC1935/2004 - all updated directives included.		
BOTTOM COVER THICKNESS	- [mm]				
TOTAL THICKNESS	2.45 [mm]				

ADDITIONAL INFORMATION	
SPECIAL FEATURES	TROUGH AND CURVE BELT
APPLICATIONS	FOOD INDUSTRY IN GENEREL FISHING INDUSTRY POULTRY SLAUGHTERHOUSES BAKERIES DAIRYWORKS FRUITS AND VEGETABLES PHARMACEUTICAL INDUSTRY
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

