


DATA SHEET POLYMAX 2T24AG

UPDATED: MAY 2012

CONSTRUCTION		DATA	
TOP COVER	Material	PVC	
	Cover structure	SMOOTH	
	Colour	APPELGREEN	
INTERMED. LAYER	Material	PVC	
	Colour	APPELGREEN	
BOTTOM COVER	Material	PVC	
	Cover	NEGATIV PYRAMIDE	
UPPER FABRIC	Warp	POLYESTER	
	Weft	POLYESTER	
INTERMED.FABRIC	Warp	-	
	Weft	-	
BOTTOM FABRIC	Warp	POLYESTER	
	Weft	POLYESTER	
TOP COVER THICKNESS		0.70 [mm]	
BOTTOM COVER THICKNESS		0.70 [mm]	
TOTAL THICKNESS		3.10 [mm]	
HARDNESS		Top cover	80 SHORE A
		Bottom cover	80 SHORE A
ANTISTATIC PROPERTIES		YES	
TEMPERTURE RANGE		Min.	-10 ° C
		Max.	70 ° C
PULLEY-DIAMETER			
WORKING TENSION (NOM.)		24 [N/mm]	
PULL FOR ELONGATION 1%		15 +/-1 [N/mm]	
WEIGHT		3.45 [Kg/m ²]	
COEF.FRICTION (STEEL)		0.57 +/-0.1	
APPROVAL		-	

ADDITIONAL INFORMATION	
SPECIAL FEATURES	TROUGH AND CURVE BELT
APPLICATIONS	FRUITS AND VEGETABLES DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ELECTRONICS INDUSTRY TEA INDUSTRY TOBACCO INDUSTRY PAPER INDUSTRY ALL ROUND TRANSPORT (MEADIUM HEAVY)
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

