


# DATA SHEET

## POLYMAX 3M0362G H EA FO

UPDATED: MAY 2012

CONSTRUCTION		DATA	
<b>TOP COVER</b>	Material	PVC	
	Cover structure	SMOOTH	
	Colour	PETROLEUM GREEN	
<b>INTERMED. LAYER</b>	Material	PVC	
	Colour	PETROLEUM GREEN	
<b>BOTTOM COVER</b>	Material	-	
	Cover	FABRIC	
	Colour	-	
<b>UPPER FABRIC</b>	Warp	POLYESTER	
	Weft	POLYESTER/MONOFIL	
<b>INTERMED.FABRIC</b>	Warp	POLYESTER	
	Weft	POLYESTER/MONOFIL	
<b>BOTTOM FABRIC</b>	Warp	POLYESTER	
	Weft	POLYESTER/MONOFIL	
<b>TOP COVER THICKNESS</b>		2.00 [mm]	
<b>BOTTOM COVER THICKNESS</b>		- [mm]	
<b>TOTAL THICKNESS</b>		4.93 [mm]	
<b>HARDNESS</b>	Top cover	87 SHORE A	
	Bottom cover	- SHORE A	
<b>ANTISTATIC PROPERTIES</b>		YES	
<b>TEMPERTURE RANGE</b>	Min.	5 ° C	
	Max.	70 ° C	
<b>PULLEY-DIAMETER</b>			
		<u>1: Normal flex</u>	
		min Ø =	150 [mm]
		<u>2: Back flex</u>	
		min Ø =	275 [mm]
<b>WORKING TENSION (NOM.)</b>		36 [N/mm]	
<b>PULL FOR ELONGATION 1%</b>		15 +/-1 [N/mm]	
<b>WEIGHT</b>		5.75 [Kg/m <sup>2</sup> ]	
<b>COEF.FRICTION (STEEL)</b>		0.15 +/- 0.03	
<b>APPROVAL</b>		-	

ADDITIONAL INFORMATION	
<b>SPECIAL FEATURES</b>	VERY RIGID OIL AND GREASE RESISTANT
<b>APPLICATIONS</b>	TRANSPORT OF HEAVY WEARING MATERIALS (CEMENT, BRICKS ECT.) METAL PROCESSING INDUSTRY (STOMPING) WOOD INDUSTRY CERAMICS INDUSTRY ALL ROUND TRANSPORT (HEAVY) GOOD RESISTANTS TO CUTTING LOADS
<b>JOINING METHODS</b>	TRIPLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING

