

DATA SHEET

POLYMAX 1E08G PU CT MAT

CONSTRUCTION			DATA		
TOP COVER	Material	HARD MAT PU	HARDNESS	Top cover	92 SHORE A
	Cover structure	SMOOTH MAT		Bottom cover	SHORE A
	Colour	GREEN	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material				
	Colour				
BOTTOM COVER	Material	PU IMPREGNATED	TEMPERATURE RANGE	Min.	-20 ° C
	Cover	FABRIC		Max.	80 ° C
	Colour		PULLEY-DIAMETER		
UPPER FABRIC	Warp			1. Normal flex	
	Weft			min. Ø =	10 [mm]
INTERMED.FABRIC	Warp			2: Back flex	
	Weft			min. Ø =	30 [mm]
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)		
TOP COVER THICKNESS		0,20 [mm]	WEIGHT		
BOTTOM COVER THICKNESS		[mm]	COEF.FRICTION (STEEL)		
TOTAL THICKNESS		0,75 [mm]	APPROVAL		

ADDITIONAL INFORMATION		
SPECIAL FEATURES	SUITABLE FOR KNIFE EDGES	
APPLICATIONS	ACCUMULATION BELT PACKING LINES PHARMACEUTICAL INDUSTRY CHEMICAL INDUSTRY ELECTRONICS INDUSTRY WOOD AND CHIPBOARD INDUSTRY PLASTICS AND EXTRUDING INDUSTRY	
JOINING METHODS	SINGLE FINGER SPLICING MECHANICAL SPLICING	