


DATA SHEET

POLYMAX 2E016BI

CONSTRUCTION			DATA		
TOP COVER	Material	FABRIC	HARDNESS	Top cover	SHORE A
	Cover structure			Bottom cover	SHORE A
	Colour	ANTRACIT	ANTISTATIC PROPERTIES		NO
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE	Min.	-10 ° C
	Colour	BLACK		Max.	90 ° C
BOTTOM COVER	Material	FABRIC	PULLEY-DIAMETER		
	Cover				
	Colour	ANTRACIT			
UPPER FABRIC	Warp	POLYESTER		1. Normal flex	
	Weft	POLYESTER/MONOFIL		min. Ø =	20 [mm]
INTERMED.FABRIC	Warp			2: Back flex	
	Weft			min. Ø =	20 [mm]
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)	16 [N/mm]	
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)	8 +/- 0,5 [N/mm]	
TOP COVER THICKNESS		[mm]	WEIGHT	1,70 [Kg/m2]	
BOTTOM COVER THICKNESS		[mm]	COEF.FRICTION (STEEL)	0,14 +/- 0,03	
TOTAL THICKNESS		1,70 [mm]	APPROVAL		

ADDITIONAL INFORMATION		
SPECIAL FEATURES		
APPLICATIONS	ALL ROUND TRANSPORT PACKING AND WRAPPING LINES ACCUMULATION BELT (LIGHT TRANSPORT) TEXTILE INDUSTRY WOOD INDUSTRY	
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	
	