

DATA SHEET

POLYMAX 2EL016G P7

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	35 SHORE A
	Cover structure	CHECKED GREEN		Bottom cover	SHORE A
	Colour	PETROL GREEN	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE	Min.	-10 ° C
	Colour	PETROL GREEN		Max.	80 ° C
BOTTOM COVER	Material	FABRIC	PULLEY-DIAMETER		
	Cover				
	Colour				
UPPER FABRIC	Warp	POLYESTER	1. Normal flex	min. Ø =	25 [mm]
	Weft	POLYESTER/MONOFIL			
INTERMED.FABRIC	Warp		2: Back flex	min. Ø =	50 [mm]
	Weft				
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)		
TOP COVER THICKNESS		0,50 [mm]	WEIGHT		
BOTTOM COVER THICKNESS		[mm]	COEF.FRICTION (STEEL)		
TOTAL THICKNESS		2,30 [mm]	APPROVAL		

ADDITIONAL INFORMATION		
SPECIAL FEATURES		
APPLICATIONS	AIRPORTS DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) PACKED GOODS (SACKS AND BOXES) WOOD AND WOOD PROCESSING INDUSTRY TOBACCO INDUSTRY PLASTIC INDUSTRY ELECTRONICS INDUSTRY	
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	

