

DATA SHEET

POLYMAX 2EL016GY MX GRIP

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	35 SHORE A
	Cover structure	FABRIC IMPRESSION		Bottom cover	SHORE A
	Colour	GREY	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	GREY			
BOTTOM COVER	Material	FABRIC	PULLEY-DIAMETER	1. Normal flex	
	Cover			min. Ø =	25 [mm]
	Colour		2. Back flex	min. Ø =	50 [mm]
UPPER FABRIC	Warp	POLYESTER			
	Weft	POLYESTER/MONOFIL	WORKING TENSION (NOM.)		
INTERMED.FABRIC	Warp		PULL FOR ELONGATION 1% (MIN.)		
	Weft		WEIGHT		
BOTTOM FABRIC	Warp	POLYESTER	COEF.FRICTION (STEEL)		
	Weft	POLYESTER	APPROVAL		
TOP COVER THICKNESS		0,50 [mm]			
BOTTOM COVER THICKNESS		[mm]			
TOTAL THICKNESS		2,20 [mm]			

ADDITIONAL INFORMATION		
SPECIAL FEATURES	HIGH ANTISTATIC VALUES	
APPLICATIONS	PACKED GOODS (LIGHT) DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ASCENDING TRANSPORT	
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	