

DATA SHEET

POLYMAX 2EL016W FDA NP

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	65 SHORE A
	Cover structure	NEGATIV PYRAMID		Bottom cover	SHORE A
	Colour	WHITE	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	WHITE			
BOTTOM COVER	Material	IMPREGNATED	PULLEY-DIAMETER	1. Normal flex	
	Cover	FABRIC		min. Ø =	30 [mm]
	Colour		2. Back flex	min. Ø =	60 [mm]
UPPER FABRIC	Warp	POLYESTER			
	Weft	POLYESTER/MONOFIL	WORKING TENSION (NOM.)		
INTERMED.FABRIC	Warp		PULL FOR ELONGATION 1% (MIN.)		
	Weft		WEIGHT		
BOTTOM FABRIC	Warp	POLYESTER	COEF.FRICTION (STEEL)		
	Weft	POLYESTER/MONOFIL	APPROVAL		
TOP COVER THICKNESS		0,70 [mm]			
BOTTOM COVER THICKNESS		[mm]			
TOTAL THICKNESS		2,10 [mm]			

ADDITIONAL INFORMATION		
SPECIAL FEATURES		
APPLICATIONS	FOOD INDUSTRY	
	FISHING INDUSTRY	
	RUBBER INDUSTRY (GRANULATED, POWDER)	
	WRAPPING MACHINES	
	BAKERIES (ACCUMULATION, DOUGH)	
JOINING METHODS	DOUBLE FINGER SPLICING	
	OVERLAPPED SPLICING	
	MECHANICAL SPLICING	

