


DATA SHEET

POLYMAX 2EL016W P6 FDA

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	55 SHORE A
	Cover structure	SERRATED		Bottom cover	SHORE A
	Colour	WHITE	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material	PVC			
	Colour	WHITE			
BOTTOM COVER	Material	FABRIC	TEMPERATURE RANGE	Min.	-10 ° C
	Cover			Max.	90 ° C
	Colour		PULLEY-DIAMETER		
UPPER FABRIC	Warp	POLYESTER		1. Normal flex	
	Weft	POLYESTER/MONOFIL		min. Ø =	70 [mm]
INTERMED.FABRIC	Warp			2: Back flex	
	Weft			min. Ø =	90 [mm]
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)		
TOP COVER THICKNESS		3,00 [mm]	WEIGHT		
BOTTOM COVER THICKNESS		[mm]	COEF.FRICTION (STEEL)		
TOTAL THICKNESS		5,30 [mm]	APPROVAL		
			USDA og FDA according to EU's 90/128/EU & EC1935/2004 - all updated directives included		

ADDITIONAL INFORMATION		
SPECIAL FEATURES		
APPLICATIONS	ALLROUND FOOD INDUSTRY MEAT AND POULTRY INDUSTRY ASCENDING TRANSPORT BAKERIES TOBACCO INDUSTRY TEA INDUSTRY FISH PROCESSING INDUSTRY FRUITS AND VEGETABLES (FROZEN)	
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	
		