

DATA SHEET

POLYMAX 2M24W FDA

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	65 SHORE A
	Cover structure	SMOOTH		Bottom cover	90 SHORE A
	Colour	WHITE	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material	PVC	TEMPERATURE RANGE		
	Colour	WHITE			
BOTTOM COVER	Material	PVC HARD	PULLEY-DIAMETER	1. Normal flex	
	Cover	NEGATIV PYRAMID		min. Ø =	50 [mm]
	Colour	WHITE	2. Back flex	min. Ø =	75 [mm]
UPPER FABRIC	Warp	POLYESTER			
	Weft	POLYESTER/MONOFIL	WORKING TENSION (NOM.)		
INTERMED.FABRIC	Warp		PULL FOR ELONGATION 1% (MIN.)		
	Weft		WEIGHT		
BOTTOM FABRIC	Warp	POLYESTER	COEF.FRICTION (STEEL)		
	Weft	POLYESTER/MONOFIL	APPROVAL		
TOP COVER THICKNESS		0,70 [mm]			
BOTTOM COVER THICKNESS		0,50 [mm]			
TOTAL THICKNESS		3,20 [mm]			

ADDITIONAL INFORMATION		
SPECIAL FEATURES	BASE FOR POLYFLEX SIDEWALLS	
APPLICATIONS	ALMOST ANY KIND OF FOODSTUFF IN GENERAL FISHING INDUSTRY POULTRY MEAT PROCESSING BAKERIES FRUITS AND VEGETABLES	
JOINING METHODS	DOUBLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	

