


DATA SHEET

POLYMAX 1M08B NDP

CONSTRUCTION			DATA					
TOP COVER	Material	PVC	HARDNESS	Top cover	55 SHORE A			
	Cover structure	NDP		Bottom cover	SHORE A			
	Colour	BLACK	ANTISTATIC PROPERTIES			YES		
INTERMED. LAYER	Material		TEMPERATURE RANGE	Min.	-10 ° C			
	Colour			Max.	80 ° C			
BOTTOM COVER	Material		PULLEY-DIAMETER					
	Cover							
	Colour			1. Normal flex				
UPPER FABRIC	Warp		min. Ø =	25	[mm]			
	Weft		2: Back flex					
INTERMED.FABRIC	Warp		min. Ø =		40			
	Weft							
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)			8 [N/mm]		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)			8 +/- 0,5 [N/mm]		
TOP COVER THICKNESS		0,70 [mm]	WEIGHT			[Kg/m2]		
BOTTOM COVER THICKNESS		[mm]	COEF.FRICTION (STEEL)			0,15 +/- 0,03		
TOTAL THICKNESS		1,85 [mm]	APPROVAL					

ADDITIONAL INFORMATION		
SPECIAL FEATURES	MAT FINISH - NO REFLECTION LOW NOISE	
APPLICATIONS	ALL ROUND FOOD TRANSPORT - ACCUMULATION ALL ROUND TRANSPORT (LIGHT/MEDIUM HEAVY) TEXTILE INDUSTRY CHECK-OUT AND WEIGHING BELT ELECTRONICS INDUSTRY WOOD AND FURNITURE INDUSTRY PLASTIC INDUSTRY PAPER AND CARDBOARD INDUSTRY	
JOINING METHODS	SINGLE FINGER SPLICING OVERLAPPED SPLICING MECHANICAL SPLICING	
	