

DATA SHEET

POLYMAX 1M12B

CONSTRUCTION			DATA		
TOP COVER	Material	PVC	HARDNESS	Top cover	80 SHORE A
	Cover structure	SMOOTH		Bottom cover	85 SHORE A
	Colour	SORT	ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material		TEMPERATURE RANGE	Min.	-15 ° C
	Colour			Max.	80 ° C
BOTTOM COVER	Material	PVC	PULLEY-DIAMETER		
	Cover	NEGATIV PYRAMIDE			
	Colour	SORT			
UPPER FABRIC	Warp		1. Normal flex	min. Ø =	30 [mm]
	Weft				
INTERMED.FABRIC	Warp		2: Back flex	min. Ø =	40 [mm]
	Weft				
BOTTOM FABRIC	Warp	POLYESTER	WORKING TENSION (NOM.)		
	Weft	POLYESTER/MONOFIL	PULL FOR ELONGATION 1% (MIN.)		
TOP COVER THICKNESS		0,60 [mm]	WEIGHT		
BOTTOM COVER THICKNESS		0,90 [mm]	COEF.FRICTION (STEEL)		
TOTAL THICKNESS		2,00 [mm]	APPROVAL		

ADDITIONAL INFORMATION	
SPECIAL FEATURES	RIGID
APPLICATIONS	AGRICULTURAL INDUSTRY DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ELECTRONICS INDUSTRY TEXTILE INDUSTRY
JOINING METHODS	SINGLE FINGER SPLICING MECHANICAL SPLICING
 	